

ILF-Series Inline Filters

AXEON ILF - Series Sediment and GAC Inline Filter Cartridges utilize a sleek encapsulated design that fits most standard water lines. AXEON ILF - Series Inline Filters feature coconut shell carbon or sediment filtration media. The carbon used in these cartridges has been specifically developed to reduce sediments, color soluble organic compounds (SOC) and volatile organic compounds (VOC).

AXEON ILF - Series Inline Filters provide solutions for a variety of applications that assist with the removal of bad taste and odor. These cartridges act as an excellent post-treatment for reverse osmosis as well as being effective for applications in ice, coffee making and refrigeration.

Benefits

- FDA Listed Materials
- Chlorine, Bad Taste, Odor Reduction
- Design Eliminates Channeling, By-Pass and Reduces Release of Carbon Fines
- Tested and Verified Performance by Independent Laboratory

Carbon ILF-2010-14-GAC

- Service Life: 2,500 gallons (9,500 liters) or est. 6 months
- Maximum Flow Rate: 0.50 gpm (1.9 lpm)
- Maximum Pressure: 100 psi
- Maximum Temperature: 100°F (38°C)
- Minimum Temperature: 35°F (2°C)

Sediment ILF-2010-14-SED

- Service Life: 2,500 gallons (9,500 liters) or est. 6 months
- Maximum Flow Rate: 0.50 gpm (1.9 lpm)
- Maximum Pressure: 100 psi
- Maximum Temperature: 100°F (38°C)
- Minimum Temperature: 35°F (2°C)

Engineered Water Treatment Solutions



Tested and Certified by NSF International against ANSI/NSF Standard 42 for material requirements only.

Applications

- Icemakers
- Reverse Osmosis Systems
- Coffee Makers
- Refrigerators

Available Port Sizes

- ¼" Female NPT Thread

| Part Number | Model | Diameter in (cm) | Length in (cm) | Ports (in) | Case Quantity | Box Dimension in (cm) | Approximate Weight by case (lbs.) |
|-------------|-----------------|------------------|----------------|------------|---------------|---|-----------------------------------|
| 200654 | ILF-2010-14-GAC | 1.95 (4.95) | 9.88 (25.10) | ¼ | 25 | 10.75 x 10.75 x 10.75 (27.30 x 27.30 x 27.30) | 15 |
| 200618 | ILF-2010-14-SED | 1.95 (4.95) | 9.88 (25.10) | ¼ | 25 | 10.75 x 10.75 x 10.75 (27.30 x 27.30 x 27.30) | 12 |



Post Treatment for Reverse Osmosis